

SAFETY WHIP CHECK

- Whip check is the low cost answer to eliminate injuries caused by broken air hose connections
- These strong steel cables prevent hose whip in case of accidental separation of coupling or clamp device
- Minimizes damage to equipment and injuries to operators in the event hose, couplings or clamps fail, or there is an accidental separation of the assembly
- Highly resistant to rust and corrosion
- No tools needed - Easy to install and remove
- "WHIP CHECK" reaches across the hose fittings to provide stand by safety for hose.
- Maximum Operating Pressure: 200 PSI

Hose-to-Tool Service



Part No.	Hose ID	Cable Dia	Length
VIT-WCT003	13-32 mm	3 mm	515 mm
VIT-WCT005	13-50 mm	5 mm	712 mm
VIT-WCT006	38-75 mm	6 mm	962 mm
VIT-WCT0010	100 mm	10 mm	1118 mm

Hose-to-Hose Service



Part No.	Hose ID	Cable Dia	Length
VIT-WCH003	13-32 mm	3 mm	515 mm
VIT-WCH005	13-50 mm	5 mm	712 mm
VIT-WCH006	38-75 mm	6 mm	962 mm
VIT-WCH0010	100 mm	10 mm	1118 mm

Material:
Wire Rope : Galvanized Carbon Steel
Ferrules : Aluminium
Springs : Galvanized Carbon Steel

Vatlit Industrial Technologies

 FF - 108, Sharnam Residency,
 Near Balaji Restaurant, Gotri - Vasna Road,
 Vadodara-390021
 Gujarat, INDIA

 +91 9725855288

 sales@vatlitindtech.in
 vatlitindtech@gmail.com

 www.vatlitindtech.in